


4-25-05

IFU



PTO/SB/21 (09-04)

Approved for use through 07/31/2006. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

21

Application Number

10/731,046

Filing Date

DECEMBER 9, 2003

First Named Inventor

HARRY STIENWAND

Art Unit

3637

Examiner Name

A, PHI DIEU TRAN

Attorney Docket Number

STIENW0301

ENCLOSURES (Check all that apply)

| | | |
|--|---|---|
| <input type="checkbox"/> Fee Transmittal Form | <input type="checkbox"/> Drawing(s) | <input type="checkbox"/> After Allowance Communication to TC |
| <input type="checkbox"/> Fee Attached | <input type="checkbox"/> Licensing-related Papers | <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences |
| <input type="checkbox"/> Amendment/Reply | <input type="checkbox"/> Petition | <input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) |
| <input type="checkbox"/> After Final | <input type="checkbox"/> Petition to Convert to a Provisional Application | <input type="checkbox"/> Proprietary Information |
| <input type="checkbox"/> Affidavits/declaration(s) | <input type="checkbox"/> Power of Attorney, Revocation | <input type="checkbox"/> Status Letter |
| <input type="checkbox"/> Extension of Time Request | <input type="checkbox"/> Change of Correspondence Address | <input type="checkbox"/> Other Enclosure(s) (please identify below): |
| <input type="checkbox"/> Express Abandonment Request | <input type="checkbox"/> Terminal Disclaimer | |
| <input type="checkbox"/> Information Disclosure Statement | <input type="checkbox"/> Request for Refund | |
| <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) | <input type="checkbox"/> CD, Number of CD(s) _____ | |
| <input type="checkbox"/> Reply to Missing Parts/Incomplete Application | <input type="checkbox"/> Landscape Table on CD | |
| <input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53 | Remarks | |
| | CANADIAN PATENT APPLICATION SERIAL No. 2,421,667 | |

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

| | | | |
|--------------|-----------------------------|----------|--------|
| Firm Name | MICHAEL BLAINE BROOKS, P.C. | | |
| Signature | <i>Michael B Brooks</i> | | |
| Printed name | MICHAEL B. BROOKS | | |
| Date | APRIL 22, 2005 | Reg. No. | 39,921 |

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

| | | | |
|-----------------------|----------------------|------|----------------|
| Signature | MARILYN BENET | | |
| Typed or printed name | <i>Marilyn Benet</i> | Date | APRIL 22, 2005 |

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application no. : 10/731,046
Applicant : Harry Stienwand
Title : Columbarium with Improved Security
Filed : December 9, 2003
Docket no. : STIENW0301
Customer no. : 24507
Confirmation No. : 6713

Date: April 22, 2005

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

REQUEST TO ENTER CERTIFIED COPY OF PRIORITY DOCUMENT

Dear Sir,

At the time the above-cited United States Nonprovisional Patent Application was filed, a claim of priority was made to Canadian Patent Application Serial No. 2,421,667. At this time, the applicant respectfully requests that the enclosed certified priority document, (i.e., Canadian Patent Application Serial No. 2,421,667) be entered into the file of the above-cited Nonprovisional Utility Patent Application

Respectfully submitted,

Dr. Michael B. Brooks
Registration No. 39,921
Telephone No. (818) 225-2920
FAX (818) 225-1569

Michael Blaine Brooks, P.C.
5010 N. Pkwy Calabasas, Suite 104
Calabasas, CA 91302-3913



Office de la propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An Agency of
Industry Canada

*Bureau canadien
des brevets
Certification*

*Canadian Patent
Office
Certification*

La présente atteste que les documents
ci-joints, dont la liste figure ci-dessous,
sont des copies authentiques des docu-
ments déposés au Bureau des brevets.

This is to certify that the documents
attached hereto and identified below are
true copies of the documents on file in
the Patent Office.

Specification and Drawings, as originally filed, with Application for Patent Serial No:
2,421,667, on March 11, 2003, by HARRY STENWAND, for "Columbarium with
Improved Security"

CERTIFIED COPY OF
PRIORITY DOCUMENT

L. Régimbald
Agent certificateur / Certifying Officer

December 8, 2003

Date

Canada

(CIPO 68)
04-09-02

OPIC  CIPO

- Page 1 -

ABSTRACT

A columbarium apparatus comprises a columbarium structure defining a plurality of niches. Each niche has an open end, and a horizontal ledge extends from the structure near the bottom wall of each niche. An inside door is configured to cover the open end of the niche and is attached by a first set of tamper resistant hardware, and an outside door is configured to cover the inside door and conceal the first set of tamper proof hardware, and is attached by a second set of tamper resistant hardware such that an inner face of the outer door is supported by an outer face of the inside door, and such that a lower edge of the outside door is supported by the ledge. A vertical channel is provided to facilitate attachment of the outside doors.

- Page 2 -

COLUMBARIUM WITH IMPROVED SECURITY

This invention is in the field of columbaria for storing cremains, and in particular systems for securing such columbaria against tampering.

5

BACKGROUND

It is commonly known to store cremains in above ground in a columbarium. To be attractive to families, it is desired that these columbaria have an appearance of permanence, dignity, and security where the remains of a loved one can be secure.

10

Such columbaria are disclosed, for example in United States Patent Numbers 6,250,025 to Darby, 5,979,124 to Branan, 5,881,505 to Larkin, III et al., and 5,195,812 to Eickhof, and in Canadian Patent Application Number 2,270,697 of Mainville. The disclosed columbaria generally comprise a plurality of boxes, commonly referred to as niches, in an array of closely adjacent rows and columns. The niches are of a size to accommodate a cremains urn, and have an open front end for insertion of the urn that is conventionally closed by a relatively thin stone door. A dust door is often placed in the open end of the niche prior to installing the outer door to prevent the entry of dust and insects.

15
20

Stone, such as granite, is preferred for the doors because of its attractive and enduring appearance, however as can be seen in the above prior art, such doors are relatively thin

- Page 3. -

in order to maintain the doors at a manageable weight, and reduce cost. As a result the stone doors can be broken by vandals without great difficulty.

The outer door, as illustrated in the disclosures of Darby, Branam, Bickhof, and Mainville, is secured to the columbaria by tamper-proof hardware such as screws, brackets, hooks, or the like to close the front of the niche in a manner that at least makes removal difficult without special tools. Branam and Mainville are directed particularly to providing door attachment systems that prevent removal of the door by vandals or other unauthorized personnel. These prior systems however do not address the fragility of the stone doors themselves, which are often broken by vandals. Once the stone door is broken, the urn is exposed and subject to theft or damage.

SUMMARY OF THE INVENTION

It is the object of the present invention to provide a columbarium apparatus that overcomes problems in the prior art. It is a further object of the present invention to provide such a columbarium apparatus that improves security of the cremains stored therein by providing an inner door, preferably of aluminum, behind and supporting an outer door, generally desired to be stone. It is a further object of the present invention to provide such a columbarium apparatus wherein stone doors are more conveniently attached to the structure.

- Page 4 -

In a first aspect the invention provides a columbarium apparatus comprising at least one niche defined by a columbarium structure, and having an open end. An inside door is configured to cover the open end of the niche and is attached to the columbarium structure by a first set of tamper resistant hardware. An outside door is configured to cover the inside door and is attached to the columbarium structure by a second set of tamper resistant hardware such that an inner face of the outside door is supported by an outer face of the inside door.

In a second aspect the invention provides a columbarium apparatus comprising a columbarium structure defining a plurality of niches. Each niche is defined by top, bottom, right side, left side, and rear walls and has an open end. A horizontal ledge extends from the columbarium structure in proximity to the bottom wall of each niche. An inside door is configured to cover the open end of the niche and is attached to the columbarium structure by a first set of tamper resistant hardware, and an outside door is configured to cover the inside door and conceal the first set of tamper proof hardware, and is attached to the columbarium structure by a second set of tamper resistant hardware such that an inner face of the outer door is supported by an outer face of the inside door, and such that a lower edge of the outside door is supported by the ledge.

The invention improves security of the stored cremains by increasing the difficulty experienced by unauthorized persons attempting to gain access to the cremains. A

- Page 5 -

vertical channel along each side of the columbarium apparatus also makes installation of the doors more convenient.

DESCRIPTION OF THE DRAWINGS:

5

While the invention is claimed in the concluding portions hereof, preferred embodiments are provided in the accompanying detailed description which may be best understood in conjunction with the accompanying diagrams where like parts in each of the several diagrams are labeled with like numbers, and where:

10

Fig. 1 is a front view of a columbarium apparatus of the invention, with the doors removed;

Fig. 2 is a cross sectional view along line 2-2 in Fig. 1;

15

Fig. 3 is a cross sectional view along line 3-3 in Fig. 1;

Fig. 4 is a cross sectional view along line 4-4 in Fig. 1;

20

Fig. 5 is a cross sectional view along line 5-5 in Fig. 6;

- Page 6 -

Fig. 6 is front view of a niche of the apparatus with the doors in place over the open end of the niche;

Fig. 7 is a perspective view of the t-bar and vertical strip of the embodiment of Fig. 1.

5

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS:

Figs. 1 - 7 illustrate a columbarium apparatus 1 comprising a columbarium structure 2 that is made from aluminum panels. The aluminum provides a lightweight structure 2 that can be readily manufactured and shipped, and that is highly resistant to corrosion. The columbarium structure 2 defines a plurality of niches 4 oriented in an array of rows and columns, as illustrated, or in another desired arrangement. Each niche is defined by

top, bottom, right side, left side, and rear walls and has an open end 6.

15 A horizontal ledge 8 extends from the columbarium structure 2 in proximity to the bottom wall of each niche 4. An aluminum t-bar 10 oriented as seen in Figs. 3 and 7 conveniently provides this ledge 8. In the illustrated embodiment the open ends 6 of the niches 4 have a vertical strip 12 along each side. A channel member 14 runs vertically along each outside edge of the columbarium structure 2. The channel members 14 define
20 recesses 16 facing each other across the front of the columbarium structure 2.

- Page 7 -

An inside door 20 is configured to cover the open end 6 of the niche 4 and is attached to the columbarium structure by a first set of tamper resistant hardware, illustrated as an inside security screw 22 through a hole in the inside door 20 and screwed into a threaded hole 24 located in the t-bar 10. The embodiment illustrated shows top and bottom threaded holes 24 in the middle of the location of the inside door 20, however more holes 24 and screws 22 oriented in a different configuration could be provided if desired.

The inside security screws 22 are countersunk into the inside door 20 so as to be flush with the outer face 26 of the inside door 20, and have a head that can only be engaged by a non-standard tool that is not readily available to unauthorized personnel. Such security screws are known in different configurations that require various different tools for removal. The inside door 20 is preferably aluminum which is strong and light, and the inside security screws 22 or like hardware are made from stainless steel or brass that will not oxidize when in contact with the aluminum of the columbarium structure 2.

15

An outside door 30 is configured to cover the inside door 20 and is attached to the columbarium structure 2 by a second set of tamper resistant hardware, illustrated as comprising a rosette 32 and an outside security screw 33 screwed into threaded hole 34 in the vertical member 12. As illustrated in Fig. 6, in the middle column of niches 4, the outer doors 30 are attached by a rosette 32 on each side. For the outer columns of niches 4, the outer doors 30 slide into the recess 16 defined by the channel members 14, and so need only be secured by a single rosette 32 on the opposite side.

20

- Page 8 -

The channel member 14 conveniently and attractively reduces the number of rosettes 32 needed to secure the outer doors 30, and provides for more convenient attachment. Instead of locating holes 34 for attachment of rosettes 32 at a mid-point of the sides of the outside doors 30, the holes 34 could be located at the corners, such that each rosette could cover the corners of four adjacent outside doors, as is seen in some of the prior art.

Conveniently the outer door is supported on the ledge 8 while being attached, instead of on a lower door as in some of the prior art. The ledge 8 also thus facilitates removal of lower doors which are not required to support a door above. The ledge 8 also ensures even spacing of the outside doors 30. The bottom row of outside doors 30 conveniently rests on a base 18.

Thus in the columbarium apparatus 1 of the invention, the inner face 36 of the outside door 30 is supported by the outer face 26 of the inside door 20. Commonly it will be desired to have the outer door be made of granite or like stone which can be easily broken by vandals or the like. The inner door 20 strengthens the outer door 30 by supporting the rear face 36 thereof, making it more difficult to break. Preferably a layer of silicone compound 40 or like resilient material is placed between the inside and outside doors to cushion the outside door 30 should it be subjected to shock from a hammer or the like. The silicone also inhibits removal of the outside door 30.

- Page 9 -

In the event the outside door 30 is breached, the niche 4 is still covered by the inside door 20 which is attached with inside security screws 22 or like tamper proof hardware. Vandals must also then breach the inside door 20 as well to gain access to the niche 4.

- 5 The first set of tamper proof hardware, security screws 22 that hold the inside door in place, is concealed by the outside door 30 when the outside door 30 is installed. For added security the inside and outside security screws 22, 33 can each require a different tool for removal. Thus even if a vandal brings a tool that is suitable for removing the normally visible outside security screws 33, he will not be able to see the inside security
10 screws 22 to determine what tool is needed to remove them until after he has removed the outside door 30. Vandals are not often so well prepared and equipped, and will be stymied.

- Vandals are also not able to determine the location of the normally concealed inside
15 security screws. Where it is required for authorized personnel to gain access to a niche 4 where the outside door 30 is stuck to the inside door 20 by silicone 40 or the like, that person will know that he only has to break away a small piece of the outside door 30 above the known but concealed location of the inside security screws 22 to remove them and thus both doors 20, 30 together.

20

The foregoing is considered as illustrative only of the principles of the invention. Further, since numerous changes and modifications will readily occur to those skilled in

- Page 10 -

the art, it is not desired to limit the invention to the exact construction and operation shown and described, and accordingly, all such suitable changes or modifications in structure or operation which may be resorted to are intended to fall within the scope of the claimed invention.

- Page 11 -

CLAIMS:

We claim:

1. A columbarium apparatus comprising:

at least one niche defined by a columbarium structure, and having an open end ;

an inside door configured to cover the open end of the niche and attached to the columbarium structure by a first set of tamper resistant hardware;

an outside door configured to cover the inside door and attached to the columbarium structure by a second set of tamper resistant hardware such that an inner face of the outside door is supported by an outer face of the inside door.

2. The apparatus of Claim 1 further comprising a ledge extending from the columbarium structure and oriented such that a lower edge of the outside door is supported by the ledge.

- Page 12 -

3. The apparatus of any one of Claims 1 and 2 wherein the outside door is attached to the columbarium structure by attachment to a vertical strip portion of the columbarium structure.
4. The apparatus of any one of Claims 1 - 3 further comprising a channel member adjacent to one side of the niche defining a recess oriented to accommodate an edge of the outside door.
5. The apparatus of any one of Claims 1 - 4 further comprising a resilient material between the inside and outside doors and in contact with the inner face of the outside door and the outer face of the inside door.
6. The apparatus of Claim 5 wherein the resilient material is a silicone compound.
7. The apparatus of any one of Claims 1 - 6 wherein the inside door is made from aluminum and the outside door is made from stone.
8. The apparatus of any one of Claims 1 - 7 wherein the first set of tamper proof hardware is concealed by the outside door when the outside door is installed.

- Page 13 -

9. The apparatus of any one of Claims 1 - 8 wherein the first set of tamper proof hardware requires a first tool for removal, and wherein the second set of tamper proof hardware requires a different second tool for removal.
10. A columbarium apparatus comprising:
 - a columbarium structure defining a plurality of niches;
 - wherein each niche is defined by top, bottom, right side, left side, and rear walls and has an open end;
 - a horizontal ledge extending from the columbarium structure in proximity to the bottom wall of at least one niche;
 - an inside door configured to cover the open end of the at least one niche and
 - an outside door configured to cover the inside door and conceal the first set of tamper proof hardware, and attached to the columbarium structure by a second set of tamper resistant hardware such that an inner face of the outer door is supported by an outer face of the inside door, and such that a lower edge of the outside door is supported by the ledge.

- Page 14 -

11. The apparatus of Claim 10 wherein the inside door is made from aluminum and the outside door is made from stone.
12. The apparatus of any one of Claims 10 and 11 wherein the outside door is attached to the columbarium structure by attachment to a vertical strip portion of the columbarium structure.
13. The apparatus of any one of Claims 10 - 12 further comprising a channel member adjacent to one side of the niche defining a recess oriented to accommodate an edge of the outside door.
14. The apparatus of any one of Claims 10 - 13 further comprising a resilient material between the inside and outside doors.
15. The apparatus of Claim 14 wherein the resilient material is a silicone compound.
16. The apparatus of any one of Claims 10 - 15 wherein the columbarium structure is substantially aluminum and wherein the tamper proof hardware comprises stainless steel or brass.

- Page 15 -

17. The apparatus of any one of Claims 10 - 16 wherein the first set of tamper proof hardware requires a first tool for removal, and wherein the second set of tamper proof hardware requires a different second tool for removal.

FIG. 2




FIG. 1




FIG. 3



FIG. 4




FIG. 5

